



Polypropylene Display Film

6 mil 100% Polypropylene “low glare” Satin Film

Common Applications: Photo Printing, Promotional Advertising Retail-POP ,
Tradeshows, Backlit, Maps, Posters, Calendars, Tags and many more.

Key Features & Benefits

- White Polypropylene offering “low glare” Satin Finish.
- Fast dry times and excellent ink adhesion.
- Water, Scratch and Tear resistant.
- Environmentally responsible: Offering the ability to recycle material subject to final application.
- Compatibility: Use with Eco, Solvent, UVC, Latex printers.

Properties: Standard size rolls: 54”x164’ on 3” cores. CSO (Coated Side Out). Custom sizes available.

| | |
|---------------|---|
| Base Material | PP Synthetic Paper |
| Gloss | Satin |
| White Point | 94 |
| Caliper | 150 ± 20 μm |
| Shelf Life | Minimum 1 year when stored at 70F (21C) at 50% RH |

Longevity: Mainly interior applications. Exterior life is short term/promo under normal conditions.

Handling: Avoid touching material on print face. Finger prints can appear in high ink areas if handled without clean gloves. Please keep material in its original packaging when not being used. Always keep away from dust, dirt and direct sunlight while stored.

Printing: 720 dpi, 8 pass will offer best results. Heater settings can vary between different equipment, Avoid overheating; 85° to 95°F is a good starting point. For the best color control, a custom profile for your RIP software should be created.

Finishing: This film does not require lamination. Pressure-sensitive laminates can be applied to increase the fade and abrasion resistance. Allow the ink to dry sufficiently before applying lamination. Product can be mounted to display board using double sided adhesive or adhesive board.

RPPFILMS-54164