

OVERLAMINATES

CAST OVERLAMINATES

LM1GL

1.5 mil. Gloss Clear Cast Vinyl • Optically Clear with UV Protection With a Permanent Acrylic Adhesive and 50# Glassine Liner

Catalina Graphic Films' Mojave Digital Media family of Overlaminates enhance overall graphic depth and gloss while protecting printed materials from UV radiation, environmental elements and general abuse.

RECOMMENDED APPLICATIONS		
•	Simple Curves	
•	Decals	
•	Fleet without Rivets	
•	Fleet with Rivets	
•	Indoor	
•	Outdoor	

OVERVIEW	
Face Film	1.5 mil. Gloss Clear Cast Vinyl
Adhesive	Permanent Acrylic
Liner	50# Glassine
Opacity	Clear
Gloss Level	Gloss
Outdoor Durability	Up to 5 Years

SPECIFICATIONS			
Application	The adhesive wets out quickly to provide a clean image. Offers excellent conformability and excellent UV protection to enhance the weathering of the underlying graphics. Can be used for overlaminating other vinyl films. Recommended use with SPMVW2 and SPMRF materials.		
Product Thickness (Film Only)	1.5 mil.		
Minimum Surface/Ambient Air Application Temperature	+ 50° F.		
Application Surface	Minimum 60° F.		
Service Temperature Range	Peak Value - 50° F. to 225° F.		
Water Resistance	No Effect.		
Chemical Resistance	No Effect.		
Adhesion	20 min.: 32 oz/in; 24 HR.:50 oz/in.		
Finish	Gloss		
Shelf Life	One (1) year when stored under conditions of 70°F and 50% relative humidity.		

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

27001 Agoura Road Phone: (818) 880-8060 Suite 100 Calabasas Hills California 91301

Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880 Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com

To order or request product samples, contact your local authorized dealer or call direct

Customer Service 800 - 333 - 3136 or visit our websites:



