



OVERLAMINATES CAST OVERLAMINATES

LM2MC

2.0 mil. Matte Clear Cast Vinyl • *Optically Clear with UV Protection*
With a Permanent Acrylic Adhesive and a 50# Kraft Liner with UV Protection

Catalina Graphic Films' Mojave Digital Media family of Overlaminates enhance overall graphic depth and gloss while protecting printed materials from UV radiation, environmental elements and general abuse.

| RECOMMENDED APPLICATIONS |
|--------------------------|
| • Simple Curves |
| • Decals |
| • Fleet without Rivets |
| • Fleet with Rivets |
| • Indoor |
| • Outdoor |

| OVERVIEW | |
|---------------------------|---------------------------------|
| Face Film | 2.0 mil. Matte Clear Cast Vinyl |
| Adhesive | Permanent Acrylic |
| Liner | 50# Kraft with UV Protection |
| Opacity | Clear |
| Gloss Level | Matte |
| Outdoor Durability | Up to 5 Years |

| SPECIFICATIONS | |
|--|--|
| Application | Offering maximum flexibility, the matte finish of the cast vinyl film reduces glare and still provides an excellent view of the underlying image. The stabilized vinyl film offers excellent protection from UV radiation. The overlaminate adhesive wets out quickly to provide a clean image. Can be used for overlaminating other vinyl films. Recommended use with SPMVW2 and SPMRF materials. |
| Product Thickness (Film Only) | 2.0 mil. |
| Minimum Surface/Ambient Air Application Temperature | + 50° F. |
| Application Surface | + 50° F. |
| Service Temperature Range | - 50° F. to 225° F. |
| Water Resistance | Excellent. |
| Chemical Resistance | Distilled water (24 hrs.) no effect; Detergent (24 hrs.) no effect; Gasoline (10 minutes) no effect. |
| Adhesion | 20 min.: 32 oz/in; 24 HR.:50 oz/in. |
| Finish | Matte |
| Shelf Life | One (1) year when stored properly at 73° F and 50% relative humidity. |

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples,
 contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:



27001 Agoura Road Suite 100
 Calabasas Hills California 91301
 Phone: (818) 880-8060
 Fax: (818) 880-1144
 Atlanta Sales: (800) 922-5880
 Chicago Sales: (800) 766-4939
 E-mail: info@catalinagraphicfilms.com

