

10 Mil Solvent Printable Polycarbonate



866 971-1008 www.bciimage.com



Developed specifically for solvent, latex and UV-curable printers, 10 Mil Solvent Printable Polycarbonate is the perfect solution for trade show graphics, point-of-purchase displays, backlit displays, floor advertising, name plates, control panels, and more. This 10 mil reverse-print material has a textured non-glare finish that's scratch resistant for a highly durable, easy-to-produce, economical, and customer-pleasing printed product.

Benefits	Applications	Customers
<ul style="list-style-type: none">• High color brilliance and high image definition.• Dimensional stability• Textured surface reduces glare	<ul style="list-style-type: none">• Tradeshow displays• ADA signage• Roll-up displays• POP graphics	<ul style="list-style-type: none">• Large format print services• Design firm/Ad agency• Exhibit houses• In-house print departments• Federal government• Schools• Sign companies• Beverage retailers

SPECIFICATIONS

Material Type	Textured polycarbonate film
Gauge	10 mil
Core Size	3" ID core
Printer/Ink Compatibility	Compatible with most low-solvent, solvent, and UV curable printers. Not recommended for HP or Seiko printers due to the inability to register clear films.
Finishing/Post Processing	Solvent inks have excellent water-resistance when used in conjunction with this film. If the film is laminated the print must dry for 24 hours to ensure that the solvents are gone from the print. Insufficient dry time can cause color shift and affect the bond strength of the laminate adhesive
RIP & Printer Media Settings	Optimized printer settings will vary from printer manufacturers. To optimize print quality, 720 dpi will offer the best results. Recommended heater settings of 122° F (50°C) for both pre and post heaters. These recommendations have been found to be a good place to start
Optimal Service Environment	For printing: 59-77° F, 20-80% relative humidity. For end use: -40 to 176° F
Ideal Storage Conditions	50-80°F, 35-65% R.H.; a controlled environment is recommended; store in original packaging.
Color	Clear
Shelf Life	Greater than one year from ship date when stored in proper conditions.

SKU	Size
-----	------

UKROMAXL3660	36" x 60 ft.
UKROMAXL5060	50" x 60 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.