

180gsm Satin Solvent PE Paper



866 971-1008 www.bciimage.com



Compatible with latex, solvent, and eco-solvent printers, this versatile production photo paper is great for large runs of photo enlargements, posters, and displays. Its economical price point and high quality results makes it ideal to use for any application. Its bright white point and satin finish give you eye catching results with colors that truly pop. The instant-dry coating helps create the most efficient workflow allowing for quick turnaround times.

Benefits	Applications	Target Customers
<ul style="list-style-type: none">• Resin coated – instant-dry• Bright white• Satin• Cost-effective	<ul style="list-style-type: none">• Point of purchase• Posters• Photo enlargements• Trade shows	<ul style="list-style-type: none">• Retail• Large format print services• Sign shops• Exhibit services

SPECIFICATIONS

Material Type	PE paper
Gauge	8 mil
Applications	Posters, Indoor displays, Photo reproductions
Product Benefits	Scratch resistant. Instant-dry
Weight	180 gsm
Whiteness	140
Opacity	90
Core Size	2" ID core
Ink Compatibility	Compatible with all inkjet printers using eco-solvent, solvent, latex, and UV-curable inks.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Water Resistance	Instant-dry and water-resistant.
Optimal Service Environment	Optimal Print Environment 70° F (21° C), 50% R.H Optimal Service Environment For printing: 60 - 80° F, 50% Relative Humidity. Handling Recommendations Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of film are supplied with the coated side facing out. Service Temp. Range -40 - 176° F (-40 C to 80° C).
Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigmented inks.
Light Fastness	The fading time of inkjet ink is a direct result of the inks you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Service Environment	70° F (21° C), 50% R.H
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Color	L 93.9 ± 1.0 a -0.3 ± 0.5 b -1.6 ± 0.7 delta b 12.4 ± 0.8
Shelf Life	1 year from the ship date when stored in proper conditions.

SKU	Size
SSPE1803600	36" x 100 ft.
SSPE1805400	54" x 100 ft.
SSPE1806100	61" x 100 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.