

225gsm Satin Solvent PE Paper



866 971-1008 www.bciimage.com



LATEX/SOLVENT/UV
—Photo Paper—

This versatile resin coated satin photo paper has been created specifically for solvent, eco-solvent, and latex printers. Your prints will instantly be dry when coming off the printer creating an efficient work environment for high production runs. It also allows you to thermally laminate this material without having to wait. With a wide color gamut and a natural satin finish, this photo paper looks exceptional when it comes to detail and quality. Whether its photo reproductions, point of purchase displays or posters, this is a perfect go-to product to give you the results you are looking for every time.

Benefits	Applications	Target Customers
<ul style="list-style-type: none">• Satin finish with wide color gamut• Can be thermally laminated• Resin Coated – Instant-Dry	<ul style="list-style-type: none">• Point of purchase• Posters• Fine Art reproduction	<ul style="list-style-type: none">• Retail• Fine Art reproduction houses• Large format print services

SPECIFICATIONS

Material Type	PE paper
Gauge	9.5 mil
Applications	Posters, Indoor displays, Photo reproductions
Product Benefits	Heavyweight which makes handling easy, instant-dry, scratch-resistant
Weight	225 gsm
Whiteness	145
Opacity	93
Core Size	2" ID core
Ink Compatibility	Compatible with all inkjet printers using eco-solvent, solvent, latex, and UV-curable inks.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Water Resistance	Instant-dry and water-resistant.
Optimal Service Environment	Optimal Print Environment 70° F (21° C), 50% R.H Optimal Service Environment For printing: 60 - 80° F, 50% Relative Humidity. Handling Recommendations Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials Rolls of film are supplied with the coated side facing out. Service Temp. Range -40 - 176° F (-40° C to 80° C).
Ink Compatibility	Compatible with all inkjet printers using eco-solvent, solvent, latex, and UV-curable inks.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Service Environment	Optimal Print Environment: 70° F (21° C), 50% R.H Optimal Service Environment for Printing: 60 -80° F, 50% Relative Humidity. Handling Recommendations: Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Color	L 93.9 ± 1.0 a -0.3 ± 0.5 b -1.6 ± 0.7 delta b 12.4 ± 0.8
Shelf Life	1 year from the ship date when stored in proper conditions.

SKU	Size
SSPE2253600	36" x 100 ft.
SSPE2255400	54" x 100 ft.
SSPE2256100	61" x 100 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.