

# 6 Mil Low Tack Clear Window Film



866 971-1008 [www.bciimage.com](http://www.bciimage.com)



A one-step adhesive solution for window graphics, 6 Mil Low Tack Clear Window Film delivers a big impact with its day- and night-viewable application. Reverse print to install on the inside of a window to protect the graphic that will be viewable from either side of the window -- indoors or out.

6 Mil Low Tack Clear Window Film creates images that really pop, especially when paired with lighting from the front or the back -- even natural sunlight will bring images to life unlike any other window film.

Ideal for retail, commercial, corporate, restaurants or department stores, this quick-dry polyester film has a dimensionally stable, lay-flat construction that can stand up to heat without shrinking or warping. Plus, it's easy to install and remove without any residue left behind.

Compatible with Latex, Solvent, and UV-curable inks.

Benefits	Applications	Customers
<ul style="list-style-type: none"><li>• Extra pop when graphics are paired with light source</li><li>• Viewable day and night from indoors or outdoors</li><li>• Removable adhesive</li><li>• One-step window graphics solution</li></ul>	<ul style="list-style-type: none"><li>• Retail stores</li><li>• Office buildings</li><li>• Restaurants</li><li>• Department stores</li><li>• Commercial environments</li></ul>	<ul style="list-style-type: none"><li>• Print Service Providers</li><li>• Design Firm /Ad Agency</li><li>• Exhibit / Display Co's.</li><li>• In-House Printers</li><li>• Beverage retailers</li></ul>

**SPECIFICATIONS**

Material Type	Polyester
Gauge	140 micron
Applications	Window clear and backlit advertisements One-step window graphics
Adhesive	Removable, Silicone
Product Benefits	Brilliant color image, high ink density absorption capacity and quick dry time
Weight	190 gsm
Finish	Matte
Core Size	3" ID Core
Optimal Service Environment	Recommended conditions for use: 15-30° C / 30-50% R.H.
Ideal Storage Conditions	It is recommended to store in the closed original packing in a cool and dry environment. Temperature: 10°-25° C, 20% R.H.
Handling Guidelines	Take cotton gloves when you handle to avoid defects and handprints. Wet application is recommended, recommend RapidTac.
Color	Clear
Ink Compatibility	Compatible with Latex, Solvent and UV-curable ink
Shelf Life	One year storage in original package under recommended storage conditions above

**SKU**
**Size**

LTWC3620	36" x 20 ft.
LTWC5400	54" x 100 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.