

# PVC-Free Banner



PVC-Free Banner is an 11.8 mil durable polyester non-woven fabric with a tight weave and semi-matte finish. This lightweight, recyclable material is an environmentally friendly alternative to vinyl banners. Ideal for indoor and short-term outdoor banners, PVC-Free Banner is also a great choice for POP displays, in-store signage and other display graphics. It's also a cost-effective alternative to traditional canvas. PVC-Free Banner is compatible with latex, UV curable, solvent, and eco-solvent inks.

Benefits	Applications	Customers
<ul style="list-style-type: none"><li>• Lightweight</li><li>• PVC-free</li><li>• Water-resistant</li><li>• Tear resistant</li></ul>	<ul style="list-style-type: none"><li>• Banners</li><li>• Canvas alternative</li><li>• POP &amp; retail displays</li><li>• Applications where PVC vinyl is prohibited</li></ul>	<ul style="list-style-type: none"><li>• Large format print service providers</li><li>• Sign companies</li></ul>

**SPECIFICATIONS**

Material	Polyester non-woven fabric
Total gauge	11.8 mil
Weight	210 ±5
Opacity	94.3%
Finish	Semi-matte
Color	L: 91 a: 3.2±1.0 b: -5.0±1.0
Whiteness	Greater than 105
Printer/Ink Compatibility	Compatible with latex, low-solvent, solvent, and UV-curable printers.
Color Matching	For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software.
Light Fastness	Fading is a direct result of the inks that you choose and the environment where the print is displayed. Check with the ink manufacture for approximate image life expectancies.
Optimal Service Environment	For printing: 60-80°F (15-30°C), 30-50% Relative Humidity.
Fastening	Can be sewn, grommited, or hemmed with Banner Tape. Grommets should be placed in the hemline along the length of the banner so that the grommet is through two layers. Corner grommets should be placed where the length and width hems cross, so that the grommet is through four layers. A reinforced corner is also recommended to increase durability.
Ideal Storage Conditions	50-77°F (10-25°C), 20% Relative Humidity. Store in original packaging.
Shelf Life	1 year from ship date when stored in proper conditions.

**SKU**
**Size**

PVCFB36	36" x 150 ft.
PVCFB42	42" x 150 ft.
PVCFB54	54" x 150 ft.
PVCFB60	60" x 150 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.