

Ultimate 385 385STL

Textured Lightblock Pop-Up Polyester Film

Applications

- Pop-up displays

Certified for
HP Latex Inks

Benefits

- Premium Pop-up material - grey back, 98% opacity
- Textured, anti-reflective bright-white front surface
- Scratch and water resistant
- No need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:



Thickness:

385 μ	15.2 mil	540 gsm
-----------------	--------------------	-------------------

Available widths:

914 36"	1270 50"
-------------------	--------------------

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies