

Event Paper / ES 150

6.5 mil. Multilayer coated, wet strength, water resistant, high white paper.

Applications:

- ❖ Vibrant Photo-realistic Image Reproduction
- ❖ Indoor signs
- ❖ Indoor short-term promotions
- ❖ Short-term outdoor
- ❖ Billboard, Advertising
- ❖ City light posters / Outdoor light box displays

Ink Compatibility:

- *Solvent
- *EcoSolvent
- * UV
- * Latex

| Part Number | Size | Core | Weight |
|---------------|-------------------|------|---------|
| ES-EP15030200 | 30"x200' | 3" | 20 lbs. |
| ES-EP15054200 | 54"x200' | 3" | 35 lbs. |
| ES-EP15063200 | 63"x200' | 3" | 40 lbs. |
| ES-EP1503020 | 30"x20' Test Roll | 3" | 2 lbs. |

Advantages

- High grade poster paper
- Excellent image quality
- Environmental friendly and recyclable

Physical Properties:

| Parameter | Value |
|--------------|----------------------|
| Caliper | 6.5 mil |
| Finish | Satin |
| Opacity | 90% |
| Total Weight | 150 g/m ² |

Frosted Window Film / LU

6 mil Matte frosted polyester film provides vivid color expression

Features and Benefits:

- ◆ Bright color
- ◆ Removable clear acrylic adhesive leaves no residue
- ◆ Backlight effect
- ◆ No UV white ink needed
- ◆ Durable

| Part Number | Size | Core | |
|-------------|----------|------|--|
| LU-FWF54100 | 54"x100' | 3" | |
| LU-FWF2720 | 27"x20' | 3" | |

Installation Suggestions:

Reverse print for indoor signage

Clean the mounting object before applying film

Wet mount application needed

Physical Properties:

| Parameter | Value |
|-------------------------|--------|
| Weight | 200gsm |
| Thickness (mil) | 6 |
| Coating | Resin |
| Base Material | PET |
| Surface | Matte |
| Adhesion @ 180, gf/inch | 300 ≤ |

Applications:

- ✓ Window privacy applications
- ✓ Retail window advertisements
- ✓ Architectural window decorations
- ✓ Indoor window advertisements

Compatibility:

* UV

* Latex

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Gloss 200 / ES

200 gsm / 7 mil High quality photo poster paper with a gloss surface.

Applications:

- ❖ POP Displays
- ❖ POS Signage
- ❖ Trade show Graphics
- ❖ Window Graphics
- ❖ Fine Art/ Photographic

Ink Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core |
|--------------|-------------------|------|
| ES-G20030150 | 30"x150' | 3" |
| ES-G20030300 | 30"x300' | 3" |
| ES-G20054150 | 54"x150' | 3" |
| ES-G20054300 | 54"x300' | 3" |
| ES-G20060150 | 60"x150' | 3" |
| ES-G20060300 | 60"x300' | 3" |
| ES-G2003020 | 30"x20' Test Roll | 3" |

Advantages

- Bright white
- Scratch resistant coating
- Water resistant
- Wide color gamut
- High resolution

Physical Properties:

| Parameter | Value | Unit |
|---------------------|--|------------------|
| Thickness | 185 ±7 | µm |
| Weight | 196 ±7 | g/m ² |
| Gloss (60°) | 44 ± 5 | % |
| Lab Values | L 96.6 ± 1.0 a 0.2 ± 0.5 b 2.5 ±0.7 *b 13.5 ± 0.8 | |
| Whiteness (D65/10°) | >140 | |
| Opacity | >90 | |
| Laminability | Hot & Cold | |

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Gloss Backlit / ES

9 mil (285 gsm) Front print polyester based film with a high gloss surface. Features a special coating for high-resolution images.

Applications:

- ❖ Indoor / Outdoor Light Boxes
- ❖ POP Displays
- ❖ Bus shelters
- ❖ Illuminated Signage
- ❖ Museums

Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core | Weight |
|-------------|-------------------|------|---------|
| ES-GBL30100 | 30"x100' | 3" | 20 lbs. |
| ES-GBL54100 | 54"x100' | 3" | 30 lbs. |
| ES-GBL60100 | 60"x100' | 3" | 33 lbs. |
| ES-GBL3010T | 30"x10' Test Roll | 3" | 2 lbs. |

Advantages

- 100% Polyester
- High gloss surface with excellent durability
- Vivid color when both lit or unlit
- Wide color gamut
- High resolution Images
- Quick dry

Physical Properties:

| Parameter | Value |
|------------|-------------|
| Thickness | 9 mil |
| LAB | 85 0 -7 |
| Print Side | Front print |

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

MatteBacklit / ES

9 mil(285 gsm)Front print polyester film with amatte surface. Features a special scratch resistant coating for high-resolution images.

Applications:

- ❖ Indoor / Outdoor Light Boxes
- ❖ POP Displays
- ❖ Bus shelters
- ❖ Illuminated Signage
- ❖ Museums
- ❖ Department Store Displays

Compatibility:

- * Eco Solvent
- * Solvent
- * UV
- * Latex

| Part Number | Size | Core | Weight |
|-------------|-------------------|------|---------|
| ES-MBL30100 | 30"x100' | 3" | 20 lbs. |
| ES-MBL54100 | 54"x100' | 3" | 30 lbs. |
| ES-MBL60100 | 60"x100' | 3" | 33 lbs. |
| ES-MBL3010T | 30"x10' Test Roll | 3" | 2 lbs. |

Advantages

- 100% Polyester
- Excellent density
- Vivid color bothwhen lit or unlit
- Wide color gamut
- Quick dry
- Bright White

Physical Properties:

| Parameter | Value |
|------------|-------------|
| Thickness | 9 mil |
| LAB | 85 1 -7 |
| Print Side | Front print |

Features

- ✓ Non PVC coating (most films have PVC coating)
- ✓ This product is Eco Friendly / Green
- ✓ Bright White Bluish

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

PhotoGloss 240 / ES

9.5 mil, 240 gsm High quality resin coated photo paper.

Features and Benefits:

- ◆ Quick drying
- ◆ RC Base
- ◆ Water resistant
- ◆ Wide color gamut
- ◆ High resolution
- ◆ Indoor / Outdoor use

| Part Number | Size | Core | Weight |
|---------------|-------------------|------|---------|
| ES-PG24054100 | 54"x100' | 3" | 25 lbs. |
| ES-PG24060100 | 60"x100' | 3" | 29 lbs. |
| ES-PG2403020 | 30"x20' Test Roll | 3" | 5 lbs. |

Applications:

- ✓ High Quality Photos
- ✓ High End Posters

Physical Properties:

| Parameter | Value |
|--------------------|----------------|
| Thickness | 9.5 mil |
| Weight | 240 gsm |
| Whiteness (WE 313) | 126.66 |
| Opacity | 98% |
| LAB | 93 1.51 -10.93 |

Compatibility:

***Latex * Eco Sol * Solvent * UV**

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

PhotoMatte 240 / ES

9.5 mil, 240 gsm High quality resin coated photo paper.

Features and Benefits:

- ◆ Quick drying
- ◆ RC Base
- ◆ Water resistant
- ◆ Wide color gamut
- ◆ High resolution
- ◆ Indoor / Outdoor use

| Part Number | Size | Core | Weight |
|---------------|-------------------|------|---------|
| ES-PM24054100 | 54"x100' | 3" | 25 lbs. |
| ES-PM24060100 | 60"x100' | 3" | 29 lbs. |
| ES-PM2403020 | 30"x20' Test Roll | 3" | 5 lbs. |

Applications:

- ✓ High Quality Photos
- ✓ High End Posters

Physical Properties:

| Parameter | Value |
|--------------------|----------------|
| Thickness | 9.5 mil |
| Weight | 240 gsm |
| Whiteness (WE 313) | 126.66 |
| Opacity | 98% |
| LAB | 93 1.51 -10.93 |

Compatibility:

***Latex * Eco Sol * Solvent * UV**

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

PhotoSatin 240 / ES

9.5 mil, 240 gsm High quality resin coated photo paper.

Features and Benefits:

- ◆ Quick drying
- ◆ RC Base
- ◆ Water resistant
- ◆ Wide color gamut
- ◆ High resolution
- ◆ Indoor / Outdoor use

| Part Number | Size | Core | Weight |
|---------------|-------------------|------|---------|
| ES-PS24054100 | 54"x100' | 3" | 25 lbs. |
| ES-PS24060100 | 60"x100' | 3" | 29 lbs. |
| ES-PS2403020 | 30"x20' Test Roll | 3" | 5 lbs. |

Applications:

- ✓ High Quality Photos
- ✓ High End Posters

Physical Properties:

| Parameter | Value |
|--------------------|----------------|
| Thickness | 9.5 mil |
| Weight | 240 gsm |
| Whiteness (WE 313) | 126.66 |
| Opacity | 98% |
| LAB | 93 1.51 -10.93 |

Compatibility:

***Latex * Eco Sol * Solvent * UV**

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

PhotoSatin 280 / ES

10 mil, 280 gsm High quality resin coated photo paper.

Applications:

- ❖ High Quality Photos
- ❖ High End Posters

Ink Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core | Weight |
|---------------|-------------------|------|---------|
| ES-PS28030150 | 30"x150' | 3" | 25 lbs. |
| ES-PS28054150 | 54"x150' | 3" | 38 lbs. |
| ES-PS28060150 | 60"x150' | 3" | 41 lbs. |
| ES-PS2803020 | 30"x20' Test Roll | 3" | 5 lbs. |

Advantages

- Quick drying
- RC Base
- Water resistant
- Wide color gamut
- High resolution
- Indoor / Outdoor use

Physical Properties:

| Parameter | Value |
|-----------|-------------|
| Thickness | 10 mil |
| Weight | 280 gsm |
| Gloss 60° | 22 |
| Opacity | 95% |
| LAB | 96 1.5 -7.5 |

Poster Paper / ES

8 mil. A multilayer coated, wet strength, water and outdoor resistant, high white paper.

Applications:

- ❖ Vibrant Photo-realistic Image Reproduction
- ❖ Indoor signs and short-term promotions
- ❖ Short-term outdoor Signage
- ❖ Billboard, Advertising
- ❖ City light posters / Outdoor light box displays

Ink Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core | Weight |
|-------------|-------------------|------|---------|
| ES-PP30165 | 30"x165' | 3" | 17 lbs. |
| ES-PP54165 | 54"x165' | 3" | 31 lbs. |
| ES-PP54300 | 54"x300' | 3" | 60 lbs. |
| ES-PP63165 | 63"x165' | 3" | 36 lbs. |
| ES-PP63300 | 63"x300' | 3" | 70 lbs. |
| ES-PP3020 | 30"x20' Test Roll | 3" | 4 lbs. |

Advantages

- Wet Strength Paper
- FSC Mix Credit Certification Code RA-COC-004253
- High Optical Density
- Scratch Resistant
- High Quality Image Reproduction
- Quick Dry

Physical Properties:

| Parameter | Value | Standard |
|--------------|--------------------------|----------|
| Total Weight | 200 g/m ² | ISO 536 |
| Thickness | 120µm (8.3mil) | ISO 534 |
| Opacity | >98% | ISO 2471 |
| Color | L*94, 3 a* 1, 3 b* -4, 4 | DIN 6174 |

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Poster PaperMatte / ES / LU

8 mil. A multilayer coated, wet strength, water and outdoor resistant, high white paper with a matte surface.

Applications:

- ❖ Vibrant Photo-realistic Image Reproduction
- ❖ Indoor signs and short-term promotions
- ❖ Short-term outdoor Signage
- ❖ Billboard, Advertising
- ❖ City light posters / Outdoor light box displays

Ink Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core |
|-------------|-------------------|------|
| ES-PPM30165 | 30"x165' | 3" |
| ES-PPM54165 | 54"x165' | 3" |
| ES-PPM62165 | 62"x165' | 3" |
| ES-PPM3020 | 30"x20' Test Roll | 3" |

Advantages

- Wet Strength Paper
- FSC Mix Credit Certification Code RA-COC-004253
- High Optical Density
- Scratch Resistant
- High Quality Image Reproduction
- Quick Dry

Physical Properties:

| Parameter | Value | Standard |
|--------------|--------------------------|----------|
| Total Weight | 200 g/m ² | ISO 536 |
| Thickness | 120µm (8.3mil) | ISO 534 |
| Opacity | >98% | ISO 2471 |
| Color | L*94, 3 a* 1, 3 b* -4, 4 | DIN 6174 |

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Poster Paper with Adhesive / ES

275 gsm with liner. A multilayer coated, wet strength, water and outdoor resistant, high white paper with permanent adhesive.

Features and Benefits:

- ◆ Wet Strength Paper
- ◆ Permanent Adhesive
- ◆ FSC Mix Credit Certification Code RA-COC-004253
- ◆ High Optical Density
- ◆ Scratch Resistant
- ◆ High Quality Image Reproduction
- ◆ Quick Dry

| Part Number | Size | Core | Weight |
|--------------|-------------------|------|---------|
| ES-PPAH30165 | 30"x165' | 3" | 25 lbs. |
| ES-PPAH54165 | 54"x165' | 3" | 45 lbs. |
| ES-PPAH60165 | 60"x165' | 3" | 49 lbs. |
| ES-PPAH3020 | 30"x20' Test Roll | 3" | 5 lbs. |

Physical Properties:

| Parameter | Value |
|--------------|---------------------------------|
| Total Weight | 275 g/m ² with liner |
| Opacity | >98% |
| Color | L*94, 3 a* 1, 3 b* -4, 4 |

Applications:

- ✓ Vibrant photo-realistic image reproduction
- ✓ Indoor signs and short-term promotions
- ✓ Short-term outdoor signage
- ✓ Billboard, Advertising
- ✓ City light posters / Outdoor light box displays

Compatibility:

* Eco Sol * Solvent * UV *Latex

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Satin 200 / ES

200 gsm / 7 mil High quality photo poster paper with a satin surface.

Applications:

- ❖ POP Displays
- ❖ POS Signage
- ❖ Trade Show Graphics
- ❖ Window Graphics
- ❖ Fine Art/ Photographic

Ink Compatibility:

- *Eco Solvent
- *Solvent
- * UV
- * Latex

| Part Number | Size | Core |
|--------------|-------------------|------|
| ES-S20030150 | 30"x150' | 3" |
| ES-S20030300 | 30"x300' | 3" |
| ES-S20054150 | 54"x150' | 3" |
| ES-S20054300 | 54"x300' | 3" |
| ES-S20060150 | 60"x150' | 3" |
| ES-S20060300 | 60"x300' | 3" |
| ES-S2003020 | 30"x20' Test Roll | 3" |

Advantages

- Bright white
- Scratch resistant coating
- Water resistant
- Wide color gamut
- High resolution

Physical Properties:

| Parameter | Value | Unit |
|---------------------|--|------------------|
| Thickness | 185 ±7 | µm |
| Weight | 196 ±7 | g/m ² |
| Gloss (60°) | 20 ± 5 | % |
| Lab Values | L 96.6 ± 1.0 a 0.2 ± 0.5 b 2.5 ±0.7 *b 13.5 ± 0.8 | |
| Whiteness (D65/10°) | >140 | |
| Opacity | >90 | |
| Laminability | Hot & Cold | |

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.