



## Océ 6POP

Pop-up Glossy Film with Grayback for Aqueous Inkjet Media for use with dye and pigment ink on thermal and piezo piezo inkjet printers.

### Product Description

Océ 6POP is a 6.8 mil high gloss, fast dry, universally compatible polyester (PET) film. Océ 6POP features a microporous, water resistant, photographic topcoat with an ultra-wide color gamut, and low dot gain. With its ultra-durable, no-tear construction and lay-flat performance, Océ 6POP is engineered to withstand repeated rolling from portable display units. The gray opaque back provides 100% opacity and eliminates image washout caused by light diffusion. Universal compatibility on Epson®, Canon®, and HP® printers.

### SPECIFICATIONS

#### Physical properties\*

- Basis Weight: 225 gsm
- Caliper: 6.8 mil
- Opacity: 100%
- Whiteness: CIE <110

\*Target Values

### Features

- Very glossy surface
- Photorealistic print results
- Excellent laminating properties

### Recommended Storage Conditions and Shelf Life

- Store in original packaging and plastic bag. Best stored in cool dry area.
- Temperature 59°-86°F. (15°-30°C).
- Relative Humidity Range 30%-70%
- Repack opened rolls when not in use
- One year at conditions noted above
- Allow material to stabilize to room conditions 24 hours before use.

### Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste can be recycled (PET). Where recycling does not exist, disposal at a landfill or an approved incinerator is recommended.

### Main Applications

- Roll up/POP-up Banners
- Trade show displays
- Commercial posters

### Printer/Ink Compatibility

Océ 6POP is recommended for use in most thermal inkjet printers by Canon, Epson, HP and also HP Latex printers.

### Media Handling

To avoid smudges and marks on your finished print we recommend handling the coated surface while wearing cotton gloves. Store unused media in original packaging, vertically. For best results,

let media acclimate to printing room conditions for 48 hours before use

### Finishing Recommendations

Océ 6POP prints may be laminated with pressure sensitive or low melt thermal laminate for additional scratch and moisture protection when needed. Best if used with thinner more flexible overlaminates.

### Important

Printer and driver setting need set up to ensure the best performance. Appropriate ink loads must be set for the ink/printer combination being used.

### ICC Color Profiles

ICC Color profiles will improve image quality and optimize ink limits for improved drytime, wider color gamut, and more accurate color matching.



# OCÉ 6POP

## Pop-up Glossy Film with Grayback Aqueous Inkjet Media for use with dye and pigment ink on thermal and piezo inkjet printers.

This information is presented as a general guide and is not a performance guarantee. The user should independently determine prior to use the suitability of the material for the specific purpose.

### Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QUANTITY PER CARTON	CORE
6POP36	36" x 100'	1 Roll	3"
6POP50	50" x 100'	1 Roll	3"

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2018 Canon Solutions America, Inc. All rights reserved.

IS-34280 CSA DS 11.8.18 CC/PDF



CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES  
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085  
ocesuppliesoc@csa.canon.com  
CSA.CANON.COM