



OCÉ WCCW7

Wall Cover Smooth and pre-pasted for Océ ColorWave® 700 printers

Product Description

Océ WCCW7 Wall Cover Smooth and pre-pasted is a PVC free digital wall product that has a pre-pasted water activated adhesive system. This allows for easy install and as easy to remove. Océ WCCW7 is an inexpensive option but durable for short term, digital color graphics for your walls. This product is compatible with Océ ColorWave 700 printers.

SPECIFICATIONS

Physical properties*

- Caliper: 10 mil
- Basis Weight: 225gsm/10pt
- Opacity: 95%
- Brightness: >88%
- ASTM E-84 Fire Rating

*Target Values

Features

- Smooth finish
- Easy Install - Easy Remove
- Excellent printability with various inks

Recommended Storage Conditions and Shelf Life

- The product should be kept in the original packaging at room temperature 60°-85°F at 45-60% relative humidity.

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- You should contact your local recycling sources for recycling this product.
- Contains 10% Post consumer waste.

Main Applications

- Murals
- Wall Décor
- POP Signage

Printer/Ink Compatibility

Océ WCCW7 is compatible with Océ ColorWave 700 printers.

Application Instructions

Please refer to finishing section below.

Finishing Recommendations

Installation

- Spray water to the back of the sheet until thoroughly saturated, or place in a dip tray.
- Gently fold the sheet with adhesive parts facing each other to keep moist and allow adhesive paste to activate.
- Set aside for 3 minutes.
- Unfold sheet and place onto a wall from top to bottom.
- Carefully smooth out bubbles and creases using a broad smoothing brush, not a squeegee, from the middle of the sheet out.

- If necessary, re-spray with water around the edges during the entire process.
- Allow surface to dry to the touch and wipe off any excess adhesive using a damp cloth or sponge.
- Trim the excess waste using a straight knife with a fresh blade tip.

Removal

- Spray the surface of the mural with water, allowing the water-based adhesive to relax for easier removal.
- Start at the top of the image and remove a 6-8" section of the panel completely, and then continue to draw the product back on itself at a 180° degree angle until the image is completely removed.
- In instances where the substrate appears to be very tightly bonded to the surface, spray more water.



OCÉ PREMIÈRE COLLECTION

For Océ ColorWave 700 printers

- After moistening the surface, allow the mural to stand for 60-90 seconds and then return to peeling the mural back upon itself.
- Use a wet cloth to remove any remaining adhesive from surface.

This information is presented as a general guide and is not a performance guarantee. The user should determine prior to use the suitability of the material for the specific application or purpose.

Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QTY. PER CARTON	CORE
WCCW730100	30" x 100'	1 Roll	3"

Canon is a registered trademark of Canon Inc. in the United States and elsewhere. "Océ" is a trademark or registered trademark of Océ-Technologies B.V. in the United States and elsewhere. Océ ColorWave is a registered trademark of Océ-Technologies B.V. in the United States and elsewhere. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. © 2018 Canon Solutions America, Inc. All rights reserved.

IS-34239 CSA DS 8.22.18 CC/PDF



CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES
100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085
ocesuppliesoc@csa.canon.com

CSA.CANON.COM