



# Series 2950 CalMask

## Series 2950: Perforated

### APPLICATIONS & FEATURES

- Specially formulated white calendered vinyl with removable adhesive for cut out stenciling on sign faces, metal surfaces, cars, trucks, and flat or curved surfaces.
- Adhesive is compatible with wide range of banner, flexible substrates and awning fabrics with improved removability.
- Applicable for high temperature stencil/paint mask and for removable vinyl lettering.

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
ADHESION	PSTC-1 (modified for dwell time on listed test surface)	Average: oz/in (n/m)	Expected Range (oz/in(n/m)
	Stainless Steel	46 (506)	30-60 (330-660)
	Acrylic Plastic	50 (550)	35-65 (220-550)
	Glass	43 (473)	30-60 (330-660)
SHEER (MINIMUM EXPECTED)	PSTC-7 - 1 hour dwell; 1 sq in surface; 4 lb load	1 hour	
TACK	ASTM D-2979-71 (normal conditions)	45 (oz/in <sup>2</sup> ) 200 (g/sq cm)	22-80 (oz/in <sup>2</sup> ) 100-350 (g/sq cm)
FILM THICKNESS	ASTM 1593	4.4 mils ± 0.1	110-114 microns ± 0.1
SERVICE TEMPERATURE RANGE		-40°F to 175°F	-40°C to 80°C
MINIMUM APPLICATION TEMPERATURE		50°F on a clean dry surface	
STORAGE STABILITY		2 years from factory shipment 70°F (21°C) and 50 relative humidity	





\*Standard Terms & Conditions Apply








## TERMS & CONDITIONS

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

April 2014

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK  
INDIA:  4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India

 800 232 7161 / 714 540 2811  800 329 2756  
 +31 0 70 354 4311  +31 0 70 355 7721  
 +44 0 161 884 0592  +31 0 70 355 7721  
 +91 99 6755 3895

arlon.com