



UV CLEAR WINDOW PET FILM SR (USO850SR)

Details


- Optically clear polyester film
- Scratch Resistance Treated & UV printable
- Permanent Adhesive and Removable without residue
- UV Block (99%)
- Liner Options: 1 mil clear (standard), 2 mil or 4 mil clear (Optional)

*** Application Guides**

- Wet mounting application
- For Flat Glasses
- Best for indoor applications
- Clean the mounting object before applying this film

Specifications

KEY FEATURES

Length (ft)	164	Width (inch)	60", 72"
Weight (gsm)	128	Coating	Resin
Caliper (mil)	4	Base Material	PET
Inner Core (inch)	3" Plastic core	Inks	
Surface	Glossy (Clear)	Adhesion at 180', gf/inch	≤ 1500

- Optically clear PET film
- Scratch Resistance Treated
- Permanent adhesive and no residue
- 60" & 72"
- Liner: 1 mil (standard) 2, 4 mil (option)

Application

- Retail window advertisements, indoor window advertisements, retail identification signs, residential interiors, Office privacy, glass partitions and cubicles
- Architectural window decorations, Glass and Plastic flatness

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.