

ECO-SOL CLEAR BACKLIT 200 GLOSSY

(SO800W)

Details

- Optically Clear Polyester film for eco-solvent, solvent, latex and UV curable inks.
- High ink density, vivid colors with high gloss and outstanding image resolution with or without light
- Scratch resistant and waterproof with advanced coating. No need for secondary process.
- Rigid substrate for stay flat and curl-free
- Excellent material for white acrylic backlit plate

Specifications

Length (ft)	100	Width (inch)	54"/60"
Weight (gsm)	285	Coating	Resin
Caliper (mil)	8.2	Base Material	PET
Inner Core (inch)	3	Printer	ESLUV
Surface	Clear		

KEY FEATURES

- Optically Clear PET
- High Ink Load
- Eco-sol, Latex & UV printable
- Excellent Rigidity (8.2 mil)
- Scratch-Resistant & Curl-free

Application

- Light box graphic, Backlit trade show display, Luminous advertising, Department store display, Bus Shelter & Metro illuminated signage
- White Acrylic Backlit Plate

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- [ICC Profiles are available](#) by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.